

Exhibit 1



US007159766B2

(12) **United States Patent**
Wurzburg et al.

(10) **Patent No.:** **US 7,159,766 B2**
(45) **Date of Patent:** ***Jan. 9, 2007**

(54) **PERIPHERAL DEVICE FEATURE
ALLOWING PROCESSORS TO ENTER A
LOW POWER STATE**

(75) Inventors: **Henry Wurzburg**, Austin, TX (US);
Tetsuo Yamamoto, Sagamihara (JP);
Mark Colman Atchison, East
Northport, NY (US)

(73) Assignee: **Standard Microsystems Corporation**,
Hauppauge, NY (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 167 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **10/762,767**

(22) Filed: **Jan. 20, 2004**

(65) **Prior Publication Data**

US 2005/0156038 A1 Jul. 21, 2005

(51) **Int. Cl.**
G06F 7/00 (2006.01)

(52) **U.S. Cl.** **235/376**; 235/439; 235/441

(58) **Field of Classification Search** 235/382,
235/435, 376, 382.5, 439, 441
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | |
|-------------|---------|------------------|
| 4,390,964 A | 6/1983 | Horky et al. |
| 5,541,985 A | 7/1996 | Ishii et al. |
| 5,630,081 A | 5/1997 | Rybicki et al. |
| 5,786,769 A | 7/1998 | Coteus et al. |
| 5,793,359 A | 8/1998 | Ushikubo |
| 5,815,426 A | 9/1998 | Jigour et al. |
| 5,841,654 A | 11/1998 | Verissimo et al. |
| 5,877,483 A | 3/1999 | Bilich et al. |

| | | |
|----------------|---------|-----------------------------|
| 5,953,511 A | 9/1999 | Sescila, III et al. |
| 6,000,607 A | 12/1999 | Ohki et al. |
| 6,168,077 B1 | 1/2001 | Gray et al. |
| 6,230,277 B1 * | 5/2001 | Nakaoka et al. 713/320 |
| 6,279,060 B1 | 8/2001 | Luke et al. |
| 6,317,839 B1 | 11/2001 | Wells |
| 6,349,878 B1 | 2/2002 | Imai |
| 6,389,544 B1 | 5/2002 | Katagiri |
| 6,405,362 B1 * | 6/2002 | Shih et al. 717/174 |
| 6,435,904 B1 | 8/2002 | Herbst et al. |
| 6,438,638 B1 | 8/2002 | Jones et al. |

(Continued)

FOREIGN PATENT DOCUMENTS

| | | |
|----|------------|---------|
| JP | 07334633 A | 12/1995 |
| JP | 08050463 A | 2/1996 |

OTHER PUBLICATIONS

U.S. Appl. No. 10/762,684, filed Jan. 20, 2004, Wurzburg.

(Continued)


Primary Examiner—Seung Ho Lee

(74) *Attorney, Agent, or Firm*—Meyertons Hood Kivlin
Kowert & Goetzel, P.C.; Jeffrey C. Hood; Russell E.
Henrichs

(57) **ABSTRACT**

If a USB device is turned off or is not active, the device may be electrically disconnected from a USB host controller. The device may be electrically disconnected through a physical interface on the device. In some embodiments, if the device becomes active during a wait period (e.g., 2–3 seconds) prior to electrically disconnecting the device, the device may not be electrically disconnected. In some embodiments, when the device is electrically disconnected from the USB host controller and no system activity of a bus mastering peripheral is occurring, the CPU may enter a low power state if other conditions are met. In some embodiments, if the USB device becomes active after electrically disconnecting, the electrical disconnection may be discontinued.

82 Claims, 10 Drawing Sheets



U.S. PATENT DOCUMENTS

6,460,143 B1 * 10/2002 Howard et al. 713/323
 6,467,042 B1 10/2002 Wright et al.
 6,505,267 B1 1/2003 Luke et al.
 6,510,524 B1 1/2003 Osburn et al.
 6,519,669 B1 2/2003 Yanagisawa
 6,557,754 B1 5/2003 Gray et al.
 6,598,100 B1 7/2003 Shu et al.
 6,601,180 B1 7/2003 Paredes et al.
 6,654,841 B1 11/2003 Lin
 6,714,215 B1 3/2004 Flora et al.
 6,910,627 B1 6/2005 Simpson-Young et al.
 6,928,562 B1 * 8/2005 Cohen et al. 713/320
 2002/0155893 A1 10/2002 Swanberg et al.
 2003/0058284 A1 3/2003 Toh et al.

2003/0167345 A1 * 9/2003 Knight et al. 709/249
 2004/0027879 A1 * 2/2004 Chang 365/200
 2004/0163303 A1 8/2004 Dutton et al.
 2005/0156038 A1 7/2005 Wurzburg et al.

OTHER PUBLICATIONS

"The Laptop Computer May Be Unable to Enter the C3 Processor Power-Saving State", <http://support.microsoft.com/default.aspx?scid=kbjen-us;297045>, date unknown (Sep. 28, 2004 listed on article but their were earlier revisions).

"The Laptop Computer May Be Unable to Enter the C3 Processor Power-Saving State", originally downloaded from: <http://support.microsoft.com/default.aspx?scid=kbjen-us;297045>; (Article publication date is unknown).

* cited by examiner





FIG. 1

**FIG. 2**




FIG. 3




FIG. 4





FIG. 5

**FIG. 6**







FIG. 7

**FIG. 8**

**FIG. 9**

**FIG. 10**

1

PERIPHERAL DEVICE FEATURE ALLOWING PROCESSORS TO ENTER A LOW POWER STATE

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to the field of computer systems and, more particularly, to peripheral devices.

2. Description of the Related Art

The Universal Serial Bus (USB) allows coupling of peripheral devices to a computer system. USB is a serial cable bus for data exchange between a host computer and a wide range of simultaneously accessible devices. The bus allows peripherals to be attached, configured, used, and detached while the host is in operation. For example, a card reader for reading flash memory cards may be coupled to a host computer through the USB. USB based systems may require that a USB host controller be present in the host system, and that the operating system (OS) of the host system support USB and USB Mass Storage Class Devices. A USB hub may be coupled to a USB host controller to allow multiple USB devices to be coupled to the host system through the USB host controller. In addition, other USB hubs may be coupled to the USB hub to provide additional USB device connections to the USB host controller.

In recent years the electronics marketplace has seen a proliferation of appliances and personal electronics devices that use solid-state memory. For example, traditional film cameras have been losing market share to digital cameras capable of recording images that may be directly downloaded to and stored on personal computers (PCs). The pictures recorded by digital cameras can easily be converted to common graphics file formats such as Joint Photographic Experts Group (JPEG), Graphic Interchange Format (GIF) or Bitmap (BMP), and sent as e-mail attachments or posted on web pages and online photo albums. Many digital cameras are also capable of capturing short video clips in standard digital video formats, for example Moving Picture Experts Group (MPEG), which may also be directly downloaded and stored on personal computers (PCs) or notebook computers. Other devices that typically use solid-state memory include personal digital assistants (PDAs), pocket PCs, video game consoles and Moving Picture Experts Group Layer-3 Audio (MP3) players.

The most widely used solid-state memory devices include flash-memory chips configured on a small removable memory card, and are commonly referred to as flash-memory cards. The majority of flash-memory cards currently on the market are typically one of: Compact Flash™, MultiMediaMemory™ memory card (MMC) and the related Secure Digital Memory card (SD), SmartMedia™ memory card (SM), xD Picture Cards™ (xD), and Memory Stick™. Most digital cameras, for example, use Compact Flash™ memory cards to record images. Many PDA models use Memory Stick™ memory cards to hold data. Some MP3 players store music files on SM memory cards. Generally, data saved by PDAs and other handheld devices using flash-memory cards are also transferred or downloaded to a PC. In the present application, the term "flash-memory" is intended to have the full breadth of its ordinary meaning, which generally encompasses various types of non-volatile solid-state memory devices as described above.

Typically, a flash-memory card can easily be removed from the utilizing device. For example, a Compact Flash™ memory card can be removed from a digital camera much like film is removed from a standard camera. The flash-

2

memory card can then be inserted into an appropriate flash-memory card reader coupled to a PC, and the image files directly copied to the PC. It should be noted that while a majority of smaller hand-held computers and PDAs have slots that receive Compact Flash™ memory cards, currently, most PCs do not, hence the need for a flash-memory card reader connecting to the PC. Most recently the preferred interface between flash-memory card readers and PCs has been the Universal Serial Bus, where the flash-memory card reader is connected to a USB port on the PC via a USB cable. Portable computer or notebook PCs typically also have PC-memory card (earlier known as Personal Computer Memory card International Association; PCMCIA) slots that can receive PCMCIA memory cards configured as flash-memory card readers.

In all, the many different memory card formats present a wide array of interface requirements not only for PCs but for other digital systems as well, such as embedded systems. Different adapters are needed for each of the memory card formats. One solution to consolidate the interfacing of flash-memory cards to desktop and portable computer PCs has been the design and manufacture of multi-format flash-memory card readers that are capable of reading the most popular formats. Such memory card-readers are sometimes referred to as "Seven-in-one" readers indicating that they may be used with the currently popular flash-memory card formats. As indicated above, such multi-format card readers are typically designed with a USB interface.

While USB devices, such as multi-format card readers and USB hubs designed with a USB interface, are typically connected to host PCs and/or notebook PCs via a USB cable, they may also be designed into computers as embedded USB devices. Typically, adding an embedded USB device, such as a card reader or hub, to a computer adversely affects power consumption of the computer. In general, a USB device attached to the USB host controller of the computer may prevent the central processing unit (CPU) of the computer from entering a low power state—e.g., the C3 state. The USB host controller, as a bus mastering peripheral, may keep the PCI bus active as long as it is attached to a USB device preventing the CPU from going into a low power state. This may especially be a problem for embedded devices (e.g., an embedded card reader). Unnecessary power may also be used to power a memory card that is not in use. When a memory card or multiple memory cards are inserted in a memory card-reader, they are normally fully powered as long as the memory card-reader is not in SUSPEND mode. In such case, the memory card can typically dissipate up to 100 mA, adversely affecting battery life.

SUMMARY OF THE INVENTION

In various embodiments, a USB device (e.g., a USB hub or card reader) coupled to a USB host controller may communicate with the USB host controller through an upstream port. In some embodiments, a USB hub may be coupled to a USB port to provide additional USB ports. Data may be transmitted from the USB device to the USB host controller and then used by a central processing unit (CPU). In some embodiments, if the USB device is turned off or is not in an active state (e.g., no cards are present in a USB card reader or no devices are attached to a USB hub), an algorithm (e.g., from the device's firmware) may be implemented to electrically disconnect the USB device from the USB host controller. In some embodiments, when the USB device is electrically disconnected from the USB host controller and no system activity from a bus mastering periph-

eral is occurring on the PCI bus, the CPU may enter a low power state (other system conditions may also need to be met).

In various embodiments, a USB device, such as a card reader, may be embedded in a portable computer, such as a laptop. The card reader may read data from memory cards inserted into the card reader. If no memory cards are inserted in the card reader, an algorithm in the card reader's firmware may be implemented to electrically disconnect the card reader from a USB host controller. In some embodiments, when the card reader is electrically disconnected from the USB host controller and no system activity from a bus mastering peripheral is occurring on the PCI bus, the CPU may be allowed to enter a low power state (other conditions may also need to be met). In some embodiments, the card reader may be electrically disconnected or electrically reconnected from the USB host controller by a sideband signal from the computer to signal the card reader when to electrically disconnect and electrically reconnect.

In some embodiments, if a card is inserted into the card reader, but has not been accessed for a first specified amount of time (e.g., 10 seconds), the card reader may power down the card. If the card is then accessed, the card reader may restore power to the card. In some embodiments, an algorithm in the card reader's firmware may power the card up and down. In some embodiments, a sideband signal may be sent to the card reader to signal the card reader to electrically disconnect after the card has been powered down. In some embodiments, the card may be powered down approximately at the same time that the card reader is electrically disconnected. In some embodiments, a sideband signal may be used to signal the card reader when to electrically reconnect.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing, as well as other objects, features, and advantages of this invention may be more completely understood by reference to the following detailed description when read together with the accompanying drawings in which:

FIG. 1 illustrates a portable computer for various embodiments;

FIG. 2 is a block diagram of one embodiment of a computer, according to an embodiment;

FIG. 3 illustrates a diagram of a card reader coupled to a USB host controller, according to an embodiment;

FIG. 4 illustrates a diagram of a USB device coupled to a USB host controller, according to an embodiment;

FIG. 5 illustrates a diagram of a hub with an attach detect logic and a physical interface, according to an embodiment;

FIG. 6 illustrates a flowchart of a method for electrically disconnecting and electrically reconnecting a device from to a USB host controller, according to an embodiment;

FIG. 7 illustrates a flowchart of a method for electrically disconnecting and electrically reconnecting a card reader to a USB host controller, according to an embodiment;

FIG. 8 illustrates a flowchart of a method for electrically disconnecting and electrically reconnecting a hub to a USB host controller, according to an embodiment;

FIG. 9 illustrates a flowchart of a method for regulating the CPU, according to an embodiment; and

FIG. 10 illustrates a flowchart of a method for regulating a CPU while attached to a hub, according to an embodiment.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will

herein be described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the present invention as defined by the appended claims. Note, the headings are for organizational purposes only and are not meant to be used to limit or interpret the description or claims. Furthermore, note that the word "may" is used throughout this application in a permissive sense (i.e., having the potential to, being able to), not a mandatory sense (i.e., must). The term "include", and derivations thereof, mean "including, but not limited to". The term "coupled" means "directly or indirectly connected".

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 illustrates an embodiment of a portable computer **101** for various embodiments. Embodiments of the invention may be used with various different types of systems of computers, and portable computer **101** is one exemplary embodiment.

In some embodiments, the portable computer **101** may be used with multiple peripheral devices such as, but not limited to, Universal Serial Bus (USB) devices (e.g., computer mouse **111**, scanners, printers, external memory devices, cameras, personal digital assistants (PDAs), keyboards, touchscreens, and joysticks). Other peripheral devices are also contemplated.

FIG. 2 is a block diagram of one embodiment of computer **101**. In some embodiments, north bridge **205** (an integrated chip) couples the central processing unit (CPU) **203** and the system memory **201** to the peripheral component interconnect (PCI) bus **207** (used to connect peripherals to the computer). As shown, south bridge **209** couples to the PCI bus **207**. In some embodiments, south bridge **209** may include a USB host controller **211** to communicate through a USB port **213** with a USB device **215**. The USB port **213** and USB device **215** may be internal or external to the computer. In some embodiments, the USB host controller **211** may provide a peripheral bus interface between the USB device **215** and the computer.

Referring again to FIG. 1, in some embodiments, USB devices, such as a card reader **113**, may communicate with a computer (e.g., portable computer **101**) through a USB host controller **211** in a PC chipset. The USB host controller **211** may regulate communication with attached USB devices (e.g., scheduling bandwidth on the bus). Communication speeds with the USB devices coupled to the USB host controller **211** may include low speed (LS), full speed (FS), and high speed (HS). In some embodiments, USB devices may be coupled to a computer (e.g., portable computer **101**) through one or more USB ports **103**. The USB ports **103** may be on the portable computer **101** or on a docking station (not shown) coupled to the portable computer **101**. A USB connector **109** may plug into a USB port **103** to couple a USB device to the portable computer **101**.

In some embodiments, a hub (not shown) may be coupled to a USB port **103** of the portable computer **101** to provide additional USB ports. An internal hub may be used to provide multiple USB ports. For example, an internal hub may provide USB ports **103a**, **103b**, and **103c**. In some embodiments, the hub may be internal to the portable computer **101**, while, in some embodiments, the internal hub may be in a docking station for the portable computer **101**.

Other external hubs may be coupled to one of the USB ports **103** to provide additional USB ports for use. Multiple hubs may be chained together to provide even more USB ports.

In some embodiments, the USB host controller **211** may detect USB devices as they are connected to a USB port **103**, interrogate the USB device (e.g., to find out what speed to use for communication with the device and device capabilities), and load a driver to support the USB device. USB devices may communicate with the USB host controller **211** using control, interrupt, bulk, and isochronous transfers. In addition, the USB device may be powered over the USB bus, while some USB devices may be self powered. When a USB device is unplugged from a USB port **103**, the USB host controller may detect the absence of the USB device and unload the driver. In some embodiments, a USB hub may not electrically connect to the USB host controller **211** until a device is coupled to the USB hub. In addition, some card readers **113** may not electrically connect to the USB host controller **211** until a card is inserted into the card reader **113**.

FIG. 3 illustrates an embodiment of a card reader **301** coupled to a USB host controller **211**. In some embodiments, a card reader **301** may be embedded in a computer, such as a portable computer **101**. The card reader **301** may communicate with a USB host controller **211** through an upstream port **305**. The card reader **301** may use a controller **325** and a physical interface **303** to assist in reading, writing, and transferring data. The memory card **309** may be inserted into the card reader **301** through memory card slot **307**. While the card reader **301** is shown with one card slot **307**, a card reader **301** with multiple card slots may also be used. In some embodiments, the memory card may be a SmartMedia™ (SM) memory card, xD Picture Cards™ (xD), a Memory Stick™, a High Speed Memory Stick (HSMS), a Memory Stick PRO™ (MSPRO), a Secure Digital (SD) memory card, a MultiMediaMemory™ memory card (MMC), NAND Flash, Compact Flash™ (CF) or a CF form-factor Advanced Technology Attachment (ATA) hard drive. Other memory cards are also contemplated. In various embodiments, a cable between an upstream port **305** and a device (not shown) may carry a power line **321**, ground **324**, and a pair of data lines **322**, **323** (D+ and D-) to transfer data between the card reader **301** and the computer. For full speed card readers, when the card reader **301** is attached to a USB port, the card reader **301** may pull the D+ line **322** high to approximately 3.3 volts using a pull up resistor (not shown) on the D+ line **322**. The USB host controller may then detect the presence of the card reader **301** on the bus and reset the card reader **301**. High speed devices connect the same way as full speed devices except, during reset, the device, such as a high speed card reader, “chirps” by driving the D- line **323** high. The USB host controller responds by alternately driving the D+ and D- lines high. When the high speed device detects the alternating chirps, the high speed device electrically removes the pull up resistor to balance the line and continues communicating at high speed. In some embodiments, the D+ and D- lines (**322**, **323**) may interact with the physical interface **303** through an attachment indicator mechanism **302**.

In some embodiments, if no memory card **309** is inserted in the card reader **301** (i.e., the card reader **301** is not in an active state) or the card reader **301** is turned off, an algorithm (e.g., stored in firmware on the card reader **301**) may be implemented in the card reader **301** to electrically disconnect the card reader **301** from the USB host controller **211**. Firmware may be on a read only memory (ROM) or a programmable read only memory (PROM) accessible by the

card reader (e.g., internal or external memory). For example, firmware may be on an Electrically Erasable Programmable Read-Only Memory (EEPROM) that may be externally attached/detached to the card reader to activate/deactivate the electrical disconnect feature. For full speed devices to electrically disconnect, the pull up resistor may be electrically removed (i.e., set to a high impedance or “tri-stated”) from the D+ line. The USB host controller may interpret this as a disconnect. To electrically disconnect high speed devices, the D+ and D- lines may both be tri-stated (set to a high impedance).

In some embodiments, when the card reader **301** is electrically disconnected from the USB host controller **211** and no system activity from a bus mastering peripheral is occurring on the PCI bus **207**, the CPU **203** may enter a low power state. In some embodiments, if a memory card **309** is in the memory card slot **307**, but has not been accessed in a first specified amount of time (e.g., 10 seconds), the memory card **309** may be powered down. In some embodiments, if a sideband signal is available, a sideband signal may be sent to signal the card reader **301** when to electrically disconnect and electrically reconnect. In one embodiment, if the card has not been accessed for a second specified amount of time (e.g., 10 minutes), the card reader **301** may be sent a sideband signal to electrically disconnect from the USB host controller **211**. In some embodiments, the card reader **301** may not electrically disconnect from the USB host controller **211** with a memory card **309** inserted unless a sideband signal can be sent to the card reader **301** to signal it to electrically connect when needed. While an embodiment of a card reader **301** is shown in FIG. 3, it is to be understood that other embodiments may include other devices with removable medium. In addition, other devices coupled to the USB host controller **211** may also be electrically disconnected as seen in FIG. 4.

FIG. 4 illustrates an embodiment of a USB device **401** coupled to a USB host controller **211**. In some embodiments, a USB device **401** may be embedded in a computer, such as a portable computer **101**. The USB device **401** may communicate with a USB host controller **211** through an upstream port **305**. In some embodiments, the USB device **401** may have a controller **325** and a physical interface **303**. Data may be transmitted from the USB device **401** to the USB host controller **211** and then used by a CPU **203**. In some embodiments, if the USB device **401** is turned off or if the device **401** is not in an active state, an algorithm may be implemented to electrically disconnect the USB device **401** from the USB host controller **211**. However, in some embodiments, the USB device **401** may not be electrically disconnected unless the USB device **401** has a way of being signaled to electrically reconnect to the USB host controller (e.g., by inserting a card into a card reader or attaching a device to a USB hub). In some embodiments, if a sideband signal can be used to signal the USB device **401** when to electrically disconnect and when to electrically reconnect, the USB device **401** may be signaled to electrically disconnect if the USB device **401** has not been used in a second specified amount of time (e.g., 10 minutes). A sideband signal may then be used to signal the USB device **401** to electrically reconnect.

In some embodiments, when the USB device **401** is electrically disconnected from the USB host controller **211** and no system activity from a bus mastering peripheral is occurring on the PCI bus **207**, the CPU **203** may enter a low power state. In some embodiments, a USB device **401** may be electrically disconnected through a physical interface on the USB device **401**. For example, as described above, the

physical interface **303** may tri-state (i.e., set to a high impedance) the D+ or the D+ and D- lines (i.e., the FS and HS transceivers) on the USB device **401** and remove any termination from the universal serial bus.

FIG. **5** illustrates a diagram of an embodiment of a hub **501** with an attach detect logic **511** and a physical interface **303**. In some embodiments, a hub **501** may be used to provide multiple downstream ports **513** for USB devices. For example, if hub **501** is internal to the portable computer **101**, downstream ports **513** may be provided through USB ports **103** (see FIG. **1**). The hub **501** may communicate through an upstream port **305** using a physical interface **303**. In some embodiments, the upstream port **305** may be an external USB port (e.g., USB port **103**), or, if the hub is internal to the portable computer **101**, may be an internal connection to a USB host controller **211**. In various embodiments, an attach detect logic **511** may be provided within the hub **501** to detect if a device is coupled to downstream ports **513**. An auto detach logic **507** may be activated by a configuration bit loaded from an EEPROM **509**. In some embodiments, the auto detach logic **507** may be activated by firmware internal to the hub **501**. In some embodiments, if the attach detect logic **511** does not detect a device coupled to the downstream ports **513**, a no ports signal **517** may be sent to the auto detach logic **507**. The auto detach logic **507** may send a detach signal **515** to the physical interface **303** if the auto detach logic **507** has been configured by a configuration bit **519** from the EEPROM **509** and receives the no ports signal **517** from the attach detect logic **511**. In some embodiments, if a device is not coupled to the hub **501**, the hub **501** may be electrically disconnected after a wait period. If a device is coupled to the hub **501** during the wait period, the hub may not be electrically disconnected.

In some embodiments, a sideband signal may be used to signal the hub **501** when to electrically disconnect and when to electrically reconnect. The hub **501** may be signaled by a sideband signal from the computer **101** to electrically disconnect if the hub **501** has not been used in a second specified amount of time (e.g., 10 minutes). A sideband signal may then be used to signal the hub **501** to electrically reconnect at a later time. In some embodiments, a sideband signal may be sent to the hub **501** when the computer goes into a SUSPEND mode to signal the hub **501** into a reduced functionality mode in which the hub **501** may only respond to a device trying to activate/wake the computer from SUSPEND mode (e.g., movement from a mouse coupled to the hub **501**). The reduced functionality mode, and other modes signaled by the sideband signal, may result in lower power usage from the hub **501**.

FIG. **6** illustrates a flowchart of an embodiment of a method for electrically disconnecting a device from a USB host controller. It should be noted that in various embodiments of the methods described below, one or more of the steps described may be performed concurrently, in a different order than shown, or may be omitted entirely. Other additional steps may also be performed as desired.

At **601**, a determination is made whether a device is coupled to the USB host controller and in an active state. For example, a card in a card reader or a device attached to a USB hub may indicate the card reader and USB hub are in active states.

At **603**, if a device is not in an active state, the device may be electrically disconnected from the USB host controller. In some embodiments, if the device is not in an active state, the device may be electrically disconnected after a wait period in case the device becomes active again relatively quickly. If the device becomes active during the wait period (e.g.,

2–3 seconds), the device may not be electrically disconnected. Other wait periods are also contemplated (e.g., 1–2 minutes, 10–20 minutes, etc.). In some embodiments, firmware may comprise algorithms to electrically disconnect the device if the device is not in an active state. However, in some embodiments, the USB device may not be electrically disconnected unless the USB device has a way of being signaled to electrically reconnect to the USB host controller (e.g., by a user inserting a card into a card reader, or receiving a sideband signal from the computer).

At **605**, if a device is in an active state, an electrical connection between the device and the USB host controller may be maintained.

At **607**, if the device enters an active state after the device is electrically disconnected, at **609**, the device may be electrically reconnected to the host controller and flow may resume at **601**. If the device is not in an active state, at **611**, the device may be maintained in an electrically disconnected state and the flow may continue at **607**.

FIG. **7** illustrates a flowchart of an embodiment of a method for electrically disconnecting a card reader from a USB host controller. It should be noted that in various embodiments of the methods described below, one or more of the steps described may be performed concurrently, in a different order than shown, or may be omitted entirely. Other additional steps may also be performed as desired.

At **701**, a determination may be made whether a memory card is in the memory card slot of a card reader coupled to the USB host controller. In other embodiments, a determination may be made as to whether a removable storage medium is in a removable storage medium's reading device.

At **703**, if there is no memory card in the memory card slot, at **705**, the card reader may be electrically disconnected from the USB host controller. In some embodiments, if there is no memory card in the card reader, the card reader may be electrically disconnected after a wait period in case the user is switching out cards, etc. If a card is inserted during the wait period (e.g., 2–3 seconds), the card reader may not be electrically disconnected. Other wait periods are also contemplated. In some embodiments, to electrically disconnect the card reader, a physical interface for the card reader may tri-state both FS and HS transmitters on the card reader and remove any termination from the universal serial bus. For example, the D+ line (full speed devices) or the D+ line and the D- line (high speed devices) may be set to a high impedance.

At **707**, if there is a memory card in the memory card slot, a determination may be made whether the memory card has been accessed in a first specified amount of time. In some embodiments, the first specified amount of time may be approximately 10 seconds. Other first specified amounts of time are also contemplated.

At **708**, if the memory card has been accessed within the first specified amount of time, the card may remain powered up and flow may continue at **707**.

At **709**, if the memory card has not been accessed within a first specified amount of time, the card may be powered down.

At **715**, if the host controller attempts to access the card, at **719**, the card may be powered up and the flow may continue at **707**.

At **717**, if the host controller is not attempting to access the card, the card may be maintained in a power down state and the flow may continue at **715**.

At **711**, after the card reader has been electrically disconnected from the USB host controller, a determination may be made whether a card has been inserted into the card reader.

At **712**, if a card has not been inserted into the card reader, the card reader may be maintained in the electrically disconnected state, and flow may continue at **711**.

At **713**, if a card has been inserted into the card reader, the card reader may be electrically reconnected and flow may continue at **707**.

FIG. **8** illustrates a flowchart of an embodiment of a method for electrically disconnecting a hub from a USB host controller. It should be noted that in various embodiments of the methods described below, one or more of the steps described may be performed concurrently, in a different order than shown, or may be omitted entirely. Other additional steps may also be performed as desired.

At **801**, a determination may be made whether a device is coupled to the hub. In some embodiments, an attach detect logic may be implemented to detect whether any devices are coupled to the hub.

At **803**, if a device is not coupled to the hub, at **805**, the hub may be electrically disconnected from the USB host controller. In some embodiments, if a device is not coupled to the hub, the hub may be electrically disconnected after a wait period to give the user time to switch out devices, etc. If a device is coupled to the hub during the wait period, the hub may not be electrically disconnected. In some embodiments, an auto detach logic may be implemented to electrically disconnect the hub from the USB host controller.

At **807**, if a device is coupled to the hub, a connection may be maintained between the hub and the USB host controller and flow may continue at **803**.

At **809**, if a device has been attached to the hub after the hub was electrically disconnected from the USB host controller, at **811**, the hub may electrically reconnect to the host controller.

At **813**, if a device has not been attached to the hub, the hub may be maintained in an electrically disconnected state and the flow may continue at **809**.

FIG. **9** illustrates a flowchart of an embodiment of a method for regulating the CPU. It should be noted that in various embodiments of the methods described below, one or more of the steps described may be performed concurrently, in a different order than shown, or may be omitted entirely. Other additional steps may also be performed as desired.

At **901**, a determination may be made whether there are any USB devices connected to the USB host controller.

At **903**, if there is a device coupled to the USB host controller, a connection between the device and the USB host controller may be maintained, and at **905**, the CPU may be maintained in an active state.

At **907**, if there are no devices coupled to the USB host controller, the USB host controller may not place a signal on the PCI bus. In some embodiments, if there is no activity on the PCI bus and other conditions for putting the CPU in a low power state are met, the CPU may go into a low power state.

FIG. **10** illustrates a flowchart of an embodiment of a method for regulating a CPU while attached to a hub. It should be noted that in various embodiments of the methods described below, one or more of the steps described may be performed concurrently, in a different order than shown, or may be omitted entirely. Other additional steps may also be performed as desired.

At **1001**, a determination may be made whether any USB devices are coupled to the hub.

At **1003**, if there are USB devices coupled to the hub, a connection may be maintained between the hub and the USB host controller, and at **1005**, the CPU may be maintained in the active state.

At **1007**, if there are no USB devices coupled to the hub, the hub may electrically disconnect from the USB host controller.

At **1009**, the USB host controller may not place a signal on the PCI bus. In some embodiments, if there is no activity on the PCI bus and other conditions for putting the CPU in a low power state are met, the CPU may go into a low power state.

As used herein, a memory medium may include any of various types of memory devices or storage devices. The term "memory medium" is intended to include an installation medium, e.g., a CD-ROM, floppy disks **104**, or tape device; a computer system memory or random access memory such as DRAM, DDR RAM, SRAM, EDO RAM, Rambus RAM, etc.; or a non-volatile memory such as a magnetic media, e.g., a hard drive, or optical storage. The memory medium may comprise other types of memory as well, or combinations thereof. In addition, the memory medium may be located in a first computer in which the programs are executed, or may be located in a second different computer which connects to the first computer over a network, such as the Internet. In the latter instance, the second computer may provide program instructions to the first computer for execution. The term "memory medium" may include two or more memory mediums which may reside in different locations, e.g., in different computers that are connected over a network. In addition, as used herein, a carrier medium—a memory medium as described above, as well as signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as a bus, network and/or a wireless link. The computer system **101** may include a memory medium(s) on which one or more computer programs or software components according to one embodiment of the present invention may be stored. For example, the memory medium may comprise a read only memory or programmable read only memory such as an EEPROM, or flash memory that stores a software program (e.g., firmware) that is executable to perform the methods described herein. Various embodiments further include receiving or storing instructions and/or data implemented in accordance with the foregoing description upon a carrier medium.

Further modifications and alternative embodiments of various aspects of the invention may be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the invention. It is to be understood that the forms of the invention shown and described herein are to be taken as the presently preferred embodiments. Elements and materials may be substituted for those illustrated and described herein, parts and processes may be reversed, and certain features of the invention may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of this description of the invention. Changes may be made in the elements described herein without departing from the spirit and scope of the invention as described in the following requests.

We claim:

1. A system, comprising:

a processor;

a host controller coupled to the processor; and

a device coupled to the host controller;

11

wherein the device is electrically disconnected from the host controller if the device is not in an active state; and wherein the device being electrically disconnected from the host controller causes an appearance to the host controller that the device is not coupled to the host controller; and

wherein a sideband signal is used to signal the device to electrically reconnect after the device has been electrically disconnected.

2. The system of claim 1, wherein the device is a card reader and the active state comprises a memory card in the card reader.

3. The system of claim 1, wherein the device is a hub and the active state comprises a second device attached to the hub.

4. The system of claim 1, wherein the device is not in an active state if the device has not been used in a second specified amount of time.

5. The system of claim 1, wherein if the device is not in an active state, the device is electrically disconnected after a wait period, wherein if the device becomes active during the wait period, the device is not electrically disconnected.

6. The system of claim 1, wherein when the device is electrically disconnected from the host controller, the device does not cause bus activity.

7. The system of claim 1, wherein the device is a card reader, and if a memory card is inserted into the card reader and the card reader has been previously electrically disconnected, the electrical disconnect from the host controller is discontinued.

8. The system of claim 1, wherein if the processor is in a low power state, the processor exits the low power state if an electrical disconnect is discontinued.

9. The system of claim 1, wherein the device is a card reader and the card reader is permanently coupled to a portable computer.

10. The system of claim 1, wherein the host controller provides a peripheral bus interface for the device.

11. The system of claim 1, wherein electrically disconnecting the device comprises electrically removing a pull up resistor from a D+ line.

12. The system of claim 1, wherein electrically disconnecting the device comprises tri-stating a D+ line and a D-line.

13. The system of claim 1, wherein the device being electrically disconnected from the host controller allows the processor to enter a low power state or remain in a low power state.

14. A method, comprising:

detecting whether a device coupled to a host controller is in an active state;

if the device is not in an active state, electrically disconnecting the device from a host controller, wherein electrically disconnecting the device from the host controller causes an appearance to the host controller that the device is not coupled to the host controller;

if the device is in an active state, maintaining an electrical connection between the device and the host controller; and

electrically reconnecting the device using a sideband signal after the device has been electrically disconnected.

15. The method of claim 14, wherein the device is a card reader, and the active state comprises a memory card inserted in the card reader.

12

16. The method of claim 14, wherein the device is a hub, and the active state comprises a second device coupled to the hub.

17. The method of claim 16, wherein the second device is coupled to the hub and a sideband signal from a computer signals the hub to electrically disconnect.

18. The method of claim 16, wherein the second device is coupled to the hub and a sideband signal from a computer signals the hub to enter a reduced functionality state and wherein a sideband signal from the computer signals the hub to exit the reduced functionality state at a later time.

19. The method of claim 14, wherein the device is not in an active state if the device has not been used in a second specified amount of time.

20. The method of claim 14, wherein if the device is not in an active state, the device is electrically disconnected after a wait period, wherein if the device becomes active during the wait period, the device is not electrically disconnected.

21. The method of claim 14, wherein if no devices are coupled to the host controller the host controller does not create bus activity.

22. The method of claim 14, wherein the device is a card reader, and wherein said electrically reconnecting is performed if a memory card is inserted into the card reader after the card reader has been electrically disconnected.

23. The method of claim 14, wherein the device is a card reader and wherein the card reader is not in an active state if the card reader has not been accessed in a second specified amount of time.

24. The method of claim 23, wherein said electrically reconnecting is performed when an attempt is made to access a card after the card reader has been electrically disconnected with a card inserted into the card reader.

25. The method of claim 14, wherein the host controller provides a peripheral bus interface for the device.

26. The method of claim 14, wherein electrically disconnecting the device comprises electrically removing a pull up resistor from a D+ line.

27. The method of claim 14, wherein electrically disconnecting the device comprises tri-stating a D+ line and a D-line.

28. A system, comprising:

a processor;

a host controller coupled to the processor;

a device detect logic;

a hub electrically coupled to the host controller and device detect logic;

an auto detach logic coupled to the hub; and

wherein the auto detach logic initiates an electrical disconnect of the hub from the host controller if the device detect logic does not detect a device on the hub, and wherein the hub being electrically disconnected from the host controller causes an appearance to the host controller that the device is not coupled to the host controller; and

wherein a sideband signal is used to signal the device to electrically reconnect after the device has been electrically disconnected.

29. The system of claim 28, wherein when the hub is electrically disconnected, the hub does not create bus activity until a device is coupled to the hub.

30. The system of claim 28, wherein if a device is coupled to the hub, the auto detach electrically reconnects the hub to the host controller.

31. The system of claim 28, wherein if the processor is in a low power state, the processor exits the low power state if the electrical disconnect is discontinued.

13

32. The system of claim 28, wherein the processor is in a portable computer.

33. The system of claim 28, wherein the hub is permanently coupled to a portable computer.

34. The system of claim 28, wherein the device comprises a keyboard, a mouse, a speaker, a microphone, a printer, a camera, a scanner, or a touchscreen.

35. The system of claim 28, wherein the device is a USB device and is coupled to the hub by plugging the device into a USB connection.

36. The system of claim 28, wherein the electrical disconnect comprises tristating the full speed (FS) and high speed (HS) transceivers.

37. The system of claim 28, wherein the electrical disconnect is enabled by a configuration bit in an Electrically Erasable Programmable Read-Only Memory (EEPROM).

38. The system of claim 28, wherein if a device is not detected on the hub, the hub is electrically disconnected after a wait period, wherein if a device is attached to the hub during the wait period, the hub is not electrically disconnected.

39. A method, comprising:

detecting whether a device is coupled to a hub;

if a device is not coupled to the hub, electrically disconnecting the hub from a host controller, wherein electrically disconnecting the hub from the host controller causes an appearance to the host controller that the device is not coupled to the host controller; and

if a device is coupled to the hub, maintaining a connection between the hub and the host controller; and electrically reconnecting the hub using a sideband signal after the hub has been electrically disconnected.

40. The method of claim 39, wherein said electrically reconnecting is performed if a device is reconnected to the hub;

wherein if the processor is in a low power state, the processor awakes from the low power state.

41. The method of claim 40, wherein the device coupled to the hub comprises a keyboard, a mouse, a speaker, a microphone, a printer, a camera, a scanner, or a touchscreen.

42. The method of claim 39, wherein electrical disconnecting comprises tristating FS and HS transceivers.

43. The method of claim 39, wherein electrical disconnect is enabled by a configuration bit in an EEPROM.

44. The method of claim 39, wherein if a device is not coupled to the hub, the hub is electrically disconnected after a wait period, wherein if a device is coupled to the hub during the wait period, the hub is not electrically disconnected.

45. A computer accessible memory medium that stores program instructions, wherein the program instructions are executable by a processor to:

detect whether a device coupled to a host controller is in an active state;

if the device is not in an active state, electrically disconnect the device from a host controller, wherein electrically disconnecting the device from the host controller causes an appearance to the host controller that a device is not coupled to the host controller; and

if the device is in an active state, maintain an electrical connection between the device and the host controller; and

electrically reconnect the device using a sideband signal after the device has been electrically disconnected.

46. The memory medium of claim 45, wherein the device is a card reader, and the active state comprises a memory card inserted in the card reader.

14

47. The memory medium of claim 45, wherein the device is a hub, and the active state comprises a second device coupled to the hub.

48. The memory medium of claim 45, wherein the device is not in an active state if the device has not been used in a second specified amount of time.

49. The memory medium of claim 45, wherein if the device is not in an active state, the device is electrically disconnected after a wait period, wherein if the device becomes active during the wait period, the device is not electrically disconnected.

50. The memory medium of claim 45, wherein if no devices are coupled to the host controller the host controller does not create bus activity.

51. The memory medium of claim 45, wherein the device is a card reader, and wherein said electrically reconnecting is performed if a memory card is inserted into the card reader after the card reader has been electrically disconnected.

52. The memory medium of claim 45, wherein the device is a card reader and wherein the card reader is not in an active state if the card reader has not been accessed in a second specified amount of time.

53. The memory medium of claim 45, wherein the device is a card reader, and wherein said electrically reconnecting is performed when an attempt is made to access a card after the card reader has been electrically disconnected with a card inserted into the card reader.

54. The memory medium of claim 45, wherein the host controller provides a peripheral bus interface for the device.

55. The memory medium of claim 45, wherein electrically disconnecting the device comprises electrically removing a pull up resistor from a D+ line.

56. The memory medium of claim 45, wherein electrically disconnecting the device comprises tri-stating a D+ line and a D- line.

57. A system, comprising:

a processor;

a host controller coupled to the processor; and

a device coupled to the host controller;

wherein the device is electrically disconnected from the host controller if the device is not in an active state; and wherein a sideband signal is used to signal the device to electrically reconnect after the device has been electrically disconnected.

58. The system of claim 57, wherein the device being electrically disconnected from the host controller makes the device appear to the host controller that the device is not coupled to the host controller.

59. The system of claim 57, wherein the device is a card reader and the active state comprises a memory card in the card reader.

60. The system of claim 57, wherein the device is not in an active state if the device has not been used in a specified amount of time.

61. The system of claim 57, wherein the device is a card reader, and if a memory card is inserted into the card reader and the card reader has been previously electrically disconnected, the electrical disconnect from the host controller is discontinued.

62. A system, comprising:

a processor;

a host controller coupled to the processor; and

a card reader coupled to the host controller;

wherein when a memory card is removed from the card reader, the card reader is electrically disconnected from the host controller; and

15

wherein the card reader being electrically disconnected from the host controller causes an appearance to the host controller that the card reader is not coupled to the host controller;

wherein a sideband signal is used to signal the card reader to electrically reconnect after the card reader has been electrically disconnected. 5

63. The system of claim 62, wherein if a memory card is inserted into the card reader and the card reader has been previously electrically disconnected, the electrical disconnect from the host controller is discontinued. 10

64. The system of claim 62, wherein the card reader being electrically disconnected from the host controller allows the processor to enter a low power state or remain in a low power state. 15

65. The system of claim 62, wherein the card reader is not in an active state if the card reader has not been used in a specified amount of time.

66. The system of claim 62, wherein if the card reader is not in an active state, the card reader is electrically disconnected after a wait period, wherein if the card reader becomes active during the wait period, the card reader is not electrically disconnected. 20

67. The system of claim 62, wherein when the card reader is electrically disconnected from the host controller, the card reader does not cause bus activity. 25

68. The system of claim 62, wherein the card reader is permanently coupled to a portable computer.

69. A method, comprising:

detecting whether a card reader coupled to a host controller is in an active state; 30

if the card reader does not have a memory card inserted in the card reader, electrically disconnecting the card reader from a host controller, wherein electrically disconnecting the card reader from the host controller causes an appearance to the host controller that the card reader is not coupled to the host controller; and 35

if the card reader is in an active state, maintaining an electrical connection between the card reader and the host controller; 40

wherein a sideband signal is used to signal the card reader to electrically reconnect when an attempt is made to access a card after the card reader has been electrically disconnected with a card inserted into the card reader.

70. The method of claim 69, wherein the card reader is not in an active state if the card reader has not been used in a specified amount of time. 45

71. The method of claim 69, wherein if the card reader is not in an active state, the card reader is electrically disconnected after a wait period, wherein if the card reader becomes active during the wait period, the card reader is not electrically disconnected. 50

72. The method of claim 69, wherein if no card reader is coupled to the host controller the host controller does not create bus activity. 55

73. The method of claim 69, wherein if a memory card is inserted into the card reader after the card reader has been electrically disconnected, the electrical disconnect is discontinued.

74. A computer accessible memory medium that stores program instructions, wherein the program instructions are executable by a processor to perform: 60

detecting whether a card reader coupled to a host controller is in an active state;

if the card reader does not have a memory card inserted in the card reader, electrically disconnecting the device from a host controller, wherein electrically disconnect- 65

16

ing the card reader from the host controller causes an appearance to the host controller that the card reader is not coupled to the host controller; and

if the card reader is in an active state, maintaining an electrical connection between the card reader and the host controller;

wherein a sideband signal is used to signal the card reader to electrically reconnect when an attempt is made to access a card after the card reader has been electrically disconnected with a card inserted into the card reader.

75. The memory medium of claim 74, wherein the card reader is not in an active state if the card reader has not been used in a specified amount of time.

76. The memory medium of claim 74, wherein if the card reader is not in an active state, the card reader is electrically disconnected after a wait period, wherein if the card reader becomes active during the wait period, the card reader is not electrically disconnected.

77. The memory medium of claim 74, wherein if no card reader is coupled to the host controller the host controller does not create bus activity.

78. The memory medium of claim 74, wherein if a memory card is inserted into the card reader after the card reader has been electrically disconnected, the electrical disconnect is discontinued.

79. A method, comprising:

detecting whether a device coupled to a host controller is in an active state, wherein the device is a hub, and the active state comprises a second device coupled to the hub;

if the device is not in an active state, electrically disconnecting the device from a host controller, wherein electrically disconnecting the device from the host controller causes an appearance to the host controller that the device is not coupled to the host controller; and

if the device is in an active state, maintaining an electrical connection between the device and the host controller; wherein the second device is coupled to the hub and a sideband signal from a computer signals the hub to electrically disconnect and wherein a sideband signal from the computer signals the hub to electrically reconnect at a later time.

80. A method, comprising:

detecting whether a device coupled to a host controller is in an active state, wherein the device is a hub, and the active state comprises a second device coupled to the hub;

if the device is not in an active state, electrically disconnecting the device from a host controller, wherein electrically disconnecting the device from the host controller causes an appearance to the host controller that the device is not coupled to the host controller; and

if the device is in an active state, maintaining an electrical connection between the device and the host controller; wherein the second device is coupled to the hub and a sideband signal from a computer signals the hub to enter a reduced functionality state and wherein a sideband signal from the computer signals the hub to exit the reduced functionality state at a later time.

81. A method, comprising:

detecting whether a device coupled to a host controller is in an active state, wherein the device is a card reader, and wherein the card reader is not in an active state if the card reader has not been accessed in a second specified amount of time;

17

if the device is not in an active state, electrically disconnecting the device from a host controller, wherein electrically disconnecting the device from the host controller causes an appearance to the host controller that the device is not coupled to the host controller; and 5
 if the device is in an active state, maintaining an electrical connection between the device and the host controller; electrically reconnecting the card reader using a sideband signal when an attempt is made to access a card after the card reader has been electrically disconnected with 10
 a card inserted into the card reader.

82. A computer accessible memory medium that stores program instructions, wherein the program instructions are executable by a processor to:

detect whether a card reader coupled to a host controller 15
 is in an active state;

18

if the card reader is not in an active state, electrically disconnect the card reader from a host controller, wherein electrically disconnecting the card reader from the host controller causes an appearance to the host controller that a card reader is not coupled to the host controller; and

if the card reader is in an active state, maintain an electrical connection between the device and the host controller;

wherein a sideband signal is used to signal the card reader to electrically reconnect when an attempt is made to access a card after the card reader has been electrically disconnected with a card inserted into the card reader.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,159,766 B2
APPLICATION NO. : 10/762767
DATED : January 9, 2007
INVENTOR(S) : Wurzburg et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims:

Column 11, Line 43, please delete “the device comprises tn-stating a D+ line”, and substitute -- the device comprises tri-stating a D+ line --.

Signed and Sealed this

Twenty-seventh Day of March, 2007

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive, stylized script. The first name "Jon" is written with a large, sweeping initial 'J'. The last name "Dudas" is written with a large, sweeping initial 'D'.

JON W. DUDAS
Director of the United States Patent and Trademark Office